


GESCHLOSSENE RECHTECKPROFILE

EN 10219



a × b [mm]	GEWICHT [kg/m]							
	WANDDICKE s [mm]							
	1,5	2,0	2,5	3,0	4,0	5,0	6,0	8,0
80 × 70		•	•	•	•			
90 × 20	•	•	•	•				
90 × 50		•	•	•	•	•	•	
90 × 60		•	•	•	•			
90 × 80		•	•	•	•	•		
100 × 20		•	•	•				
100 × 30		•	•	•				
100 × 40		•	•	•	•	•	•	
100 × 50		•	•	•	•	•	•	
100 × 60		•	•	•	•	•	•	
100 × 70		•	•	•	•	•		
100 × 80		•	•	•	•	•	•	•
103,5 × 25		•	•	•				
110 × 30		•	•	•				
120 × 30		•	•	•				
120 × 40		•	•	•	•	•	•	
120 × 50			•	•	•	•		
120 × 60		•	•	•	•	•	•	•
120 × 80		•	•	•	•	•	•	•
120 × 100					•	•	•	•
140 × 60		•	•	•	•	•	•	•
140 × 70				•	•	•	•	•
140 × 80					•	•	•	•
140 × 100					•	•	•	•
140 × 120					•	•	•	•
150 × 50			•	•	•	•	•	•
150 × 60			•	•	•	•	•	•
150 × 100					•	•	•	•
160 × 80				•	•	•	•	•
160 × 100					•	•	•	•
160 × 120				•	•	•	•	•
160 × 140					•	•	•	•
180 × 60				•	•	•	•	•
180 × 80					•	•	•	•
180 × 100					•	•	•	•
180 × 120					•	•	•	•
180 × 140					•	•	•	•
200 × 80					•	•	•	•
200 × 100					•	•	•	•
200 × 120					•	•	•	•
200 × 140					•	•	•	•
200 × 150					•	•	•	•
200 × 160					•	•	•	•
250 × 100					•	•	•	•
250 × 150						•	•	•
300 × 100						•	•	•